Technical Datasheet ROHS Tasker® C276 L.S.Z.H. – 2x2,50 mm² Halogen Free Flexible Loudspeaker Cable FirestoP®



CATEGORY Flexible Speaker Cable

APPLICATIONS Professional Loudspeakers and premade cables

A: Black Soft L.S.Z.H.sheath. Flame Retardant and Halogen Free.

Outer Diam. Ø 9,00(±0,20) mm.

B: Cores Insulation with **PVC** sheaths colored one Red and one Black.

Diam. Ø 3,50 mm (±0,20) mm.

C: O.F.C. red copper formation 80x0,20 mm.

Nom. Cross section 2x2,50 mm²

<u>MARKING</u> tasker® C276 L.S.Z.H. 2x2.50 mm² – O.F.C. Speaker Cable – Halogen Free

FirestoP® - Made In Italy

CUSTOM This product may be custom produced also in L.S.Z.H. polymer, PE, PUR,

PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	6,41 Ω/Km
Test Voltage	5 00V
Operative Temperature	-30/+70°C

USE	Х	Indoor	Interno Edificio
Impiego	Х	Outdoor Limited	Estemo Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Estemo Interrato

INSTALLATION	х	Fixed	Fissa
Posa	X	Restricted Mobile	Mobile Limitata
		Mobile	M obile
		Mobile in Dr@hain	Mobile in Catena

INFORMATION	х	RoHS2 Compliant
Informazioni	X	Ver. A / 16.05.16

YOUR DEALER



www.beglec.com